AUG 2 4 2006 -

03/11

PAGE

Appln. No. 10/646,276

Attorney Docket No. 11721-032

1. Amendments to the Claims

- (Cancelled). 1.
- 2. (Currently Amended): The apparatus according to Claim [[1]] 9, the force sensing device including an element adapted to sense a torsional load applied to in the third member, the torsional load being created in response to the tension of the seat belt.

BHGL

- 3. (Original): The apparatus according to Claim 2, the force sensing device including a printed circuit board in communication with the element.
 - 4. (Cancelled)
- 5, (Currently Amended) The apparatus according to Claim [[1]] 9, wherein the first, second and third members form an S-clip, and the S-clip forms a tooth to retain the seat belt.
- 6. (Currently Amended) The apparatus according to Claim [[1]] 5, wherein the first member forms a first leg of the S-clip, the second member forms a second leg of the S-clip, the third member forms a center section of the S-clip.



BRINKS HOFER GILSON & LIONE PO Box 10395 Chicago, IL 60610

PAGE 04/11

08/24/2006 02:57 7349946331

Appln. No. 10/646,276

Attorney Docket No. 11721-032

7. (Currently Amended): The apparatus according to Claim [[1]]

BHGL

9, the force sensing device including a light to provide a visual alert to the

operator when the tension is within the predetermined range.

8. (Currently Amended): The apparatus according to Claim [[1]]

9, the force sensing device including a tone generator to provide an audible alert

to the operator when the tension is within the predetermined range.

9. (Previously Presented): An apparatus for alerting a motor

vehicle operator that tension of a motor vehicle seat belt is within a

predetermined range, and adapted to be fastened to the seat belt, the seat belt

having a first and second web surface, the apparatus comprising:

first and second members contacting the first web surface of the

seat belt;

a third member located between the first and second members and

contacting the second web surface of the seat belt, the third member providing a

response to the tension of the seat belt;

a force sensing device coupled to the third member, the device

being adapted to alert the operator when the response of the third member

corresponds to the tension of the seat belt being within the predetermined range,

the force sensing device including a manual input in communication with an

integrated circuit to indicate when a reference tension is applied to the apparatus.

BRINKS HOFER GILSON &LIONE

BRINKS HOFER GILSON & LIONE PO Box 10395

Chicago, IL 60610

Appln. No. 10/646,276

Attorney Docket No. 11721-032

10. (Currently Amended): The apparatus according to Claim [[1]] 9, the force sensing device including a biasing member coupled to the third member.

BHGL

- 11. (Currently Amended): The apparatus according to Claim [[1]] 9, wherein the third member is displaced in response to the tension in the seat belt.
- 12. (Currently Amended): The apparatus according to Claim [[1]] 9, wherein the first member includes a roller for contacting the seat belt.
- 13. (Currently Amended): The apparatus according to Claim [[1]] 9, wherein the third member is comprised of a pin assembly having a rounded head to contact the seat belt.
- 14. (Currently Amended): The apparatus according to Claim [[1]] 9, wherein the third member includes a roller for contacting the seat belt.
- 15. (Currently Amended): The apparatus according to Claim [[1]] 9, wherein the first, second, and third members include rollers contacting the seat belt.
 - 16. (Cancelled)

08/24/2006 02:57 7349946331 BHGL PAGE 06/11

Appln. No. 10/646,276

Attorney Docket No. 11721-032

17. (Previously Presented): An apparatus for alerting a motor

vehicle operator that tension of a motor vehicle seat belt is within a

predetermined range, and adapted to be fastened to the seat belt, the seat belt

having a first and second web surface, the apparatus comprising:

first and second members contacting the first web surface of the

seat belt;

a third member located between the first and second members and

contacting the second web surface of the seat belt, the third member providing a

response to the tension of the seat belt;

a force sensing device coupled to the third member, the device

being adapted to alert the operator when the response of the third member

corresponds to the tension of the seat belt being within the predetermined range,

wherein the force sensing device includes a visual indicator to alert the operator

when the third member is displaced corresponding to a tension of the seat belt

within the predetermined range, the visual indicator including a scale

corresponding to a plurality of tension conditions.

18. (Currently Amended): The apparatus according to Claim [[1]]

17, wherein the first, second, and third member are oriented in an S shaped

configuration to form an S-clip.

19. (Cancelled)

BRINKS HOFER GILSON

ALIONE

BRINKS HOFER GILSON & LIONE

PO Box 10395

Chicago, IL 60610

Appln. No. 10/646,276

08/24/2006

Attorney Docket No. 11721-032

20. (Cancelled)

21. (Currently Amended): The apparatus according to Claim [[20]]

18, wherein the S-clip has a tooth formed by at least one of the members to

retain the seat belt.

22. (Currently Amended): The apparatus according to Claim [[20]]

18, wherein the first member includes a first leg of the S-clip, the second member

includes a second leg of the S-clip, the third member includes a center section of

the S-clip.

23. (Currently Amended): The apparatus according to Claim [[20]]

18, the device including a printed circuit board in communication with the

element.

24. (Currently Amended): The apparatus according to Claim [[20]]

17, the visual indicator device including a light to provide a visual alert to the

operator when the tension is within the predetermined range.

25. (Currently Amended): The apparatus according to Claim [[20]]

17, the device further including a tone generator to provide an audible alert to the

operator when the tension is within the predetermined range.

HOFER CILSON

BRINKS HOFER GILSON & LIONE

PO Box 10395

Chicago, IL 60610

Appln. No. 10/646,276

Attorney Docket No. 11721-032

- 26. (Currently Amended): The apparatus according to Claim [[20]] 17, the device including a manual input to indicate when a reference tension is applied to the apparatus.
- 27. (Previously Presented): An apparatus for alerting an operator a tension of a seat belt is within a predetermined range, the seat belt having a first and second web surface, the apparatus comprising:
 - a first member contacting the first web surface of the seat belt;
 - a second member contacting the first web surface of the seat belt;
- a third member located between the first and second members and contacting the second web surface of the seat belt, the third member being displaced in response to a tension in the seat belt;
- a device coupled to the third member, the device being adapted to alert an operator when the displacement of the third member corresponds to the tension of the seat belt being within the predetermined range, the device including a visual indicator to alert the operator when the third member is displaced a distance corresponding to a tension of the seat belt within the predetermined range, the visual indicator including a scale corresponding to a plurality of tension conditions.
- 28. (Original): The apparatus according to Claim 27, the device including a biasing member coupled to the third member.

Attorney Docket No. 11721-032

Appln. No. 10/646,276

29.

(Original): The apparatus according to Claim 27, wherein the biasing member biases the third member against the seat belt.

30. (Original): The apparatus according to Claim 27, wherein the first member includes a roller for contacting the seat belt.

31. (Original): The apparatus according to Claim 27, wherein the third member includes a rounded head to contact the seat belt.

32. (Original): The apparatus according to Claim 27, wherein the third member includes a roller for contacting the seat belt.

33. (Original): The apparatus according to Claim 27, wherein the first, second, and third members include rollers.

34-35. (Cancelled)

